

```

<table border="0" width="99%"> <tr> <td colspan="2"><h4>MBF - Metal Bellow Seal for
High Temperature Application</h4></td> </tr> <tr> <td colspan="2"></td> </tr> <tr> <td width="45%"><h4>Features</h4></td> <td width="49%">◆</td>
</tr> <tr> <td colspan="2" valign="top"><ul class="style1"> <li>Made from finest raw
material from best sources world wide</li> <li>Manufactured on state of the art Micro
Plasma welding equipment from Switzerland.</li> <li>Single ply double ply bellow
configurations</li> <li>Simple Designs or complex cartridge configurations possible as per
customer requirement</li> <li>Available in edge welded or hydro formed bellow design.</li>
<li>Design features include: direct drive, torsion- free drive, pumping screws, hydrodynamic
facial groves etc</li> </ul></td> </tr> <tr> <td><h4>Applications</h4></td>
<td>◆</td> </tr> <tr> <td>Industrial, Marine</td> <td>◆</td> </tr> <tr>
<td><h4>Application Data</h4></td> <td>◆</td> </tr> <tr> <td bgcolor="#cccccc">Seal
Faces</td> <td bgcolor="#cccccc">Carbon, TC, SIC etc</td> </tr> <tr> <td>Secondary
Packing</td> <td>Viton◆, Kalrez◆, Grafoil, Chemraz </td> </tr> <tr> <td
bgcolor="#cccccc">Bellow</td> <td bgcolor="#cccccc">SS 316L, Hastalloy C, Titamium,
Inconil, Monal</td> </tr> <tr> <td>Pressure</td> <td>Vacuum to 40 kg/cm2</td> </tr>
<tr> <td bgcolor="#cccccc">Temperature</td> <td bgcolor="#cccccc">upto 450◆c</td>
</tr> <tr> <td>◆</td> <td>◆</td> </tr> <tr> <td colspan="2">* For more rigorous
application consult General Seal</td> </tr> </table>

```